



Environmental Equipment, Inc

COMBUSTION GAS ANALYZERS - PRODUCT RANGE

A new standard in measuring equipment

For the continuous and simultaneous measurement of air temperature/ flue-gas temperature / O₂ / CO / CO₂ / SO₂ / NO / NO₂ / H₂S / HC / CH₄ / H₂ / NH₃ / O₃ / HCl / HCN / Cl₂ / losses / efficiency / excess air / draft / soot

Additional gases available upon request

AUTOMATIC CALIBRATION - SELF-CHECK - EASE OF OPERATION - USEABLE FOR ALL FUELS

MEASURING INSTRUMENTS FOR MANY INDUSTRIAL APPLICATIONS



IMR 1000



IMR 1400



IMR 2800

| | O ₂ | CO | CO -High | CO ₂ -Calc | CO ₂ -Measured | NO | NO ₂ | SO ₂ | H ₂ S | HC | Draft | Temp | Soot | Efficiency | Ex. Air | Losses | Dryer | Printer | Dust |
|------------------|----------------|----|----------|-----------------------|---------------------------|----|-----------------|-----------------|------------------|----|-------|------|------|------------|---------|--------|-------|---------|------|
| IMR 1000 1-4 | X | X | | X | | O | | | | | X | X | | | X | | | O | |
| IMR 1050X | X | X | | | X | | | | | | X | X | | | X | | | O | |
| IMR 1050X-NO | X | X | | | X | X | | | | | X | X | | | X | | | O | |
| IMR 1400 C/CP | X | X | O | X | O | O | S | O | S | S | O | X | O | X | X | X | | O | |
| IMR 1400 P | X | X | O | X | O | | | | | | X | X | X | X | X | X | | O | |
| IMR 1400 PL | X | X | O | X | O | X | S | | | | X | X | X | X | X | X | | X | |
| IMR 1400 PS | X | X | O | X | O | X | S | X | S | S | X | X | X | X | X | X | | X | |
| IMR 1400 IR | X | X | | | X | O | | O | | O | X | X | O | X | X | X | | X | |
| IMR 1440 FL/COFL | X | X | O | X | | O | | | | | O | X | X | X | X | X | | X | |
| IMR 2000 P | X | X | | X | O | X | O | X | S | S | X | X | O | | X | X | | X | |
| IMR 2800 P | X | X | | X | O | X | X | X | S | S | X | X | O | | X | X | | X | |
| IMR 2800 A\IR | X | X | | | X | X | S | X | S | X | O | X | O | X | X | X | | X | |
| IMR 5000 | O | O | | | O | O | O | O | O | O | O | O | | | | | | | |
| IMR 400/500 | | | | | | | | | | | | | | | | | X | | |
| DA-75 | | | | | | | | | | | | | | | | | | | X |

X = Standard Feature, O = Optional Feature, S = can switch for another sensor



IMR 5000



IMR 1400



DA-75



IMR 400

IMR 5000